



Flo Healthcare

5801 Goshen Springs Road NW
Suite A
Norcross, GA 30071-3505
USA

T (877) FLO 4040
F (678) 990 6380

Media Contact

Linda Healan
Healan PR, Inc.
T (678) 889 8057
lhealan@healanpr.com

2700 Medication Workstations

Base Cart

Footprint	21" W x 22" D
Construction	Aluminum base, column, and polymer work surface with steel support structure
Work surface	21" W x 17" D
Casters	Height adjustable from 36" to 52" Four swivel: two locking, two non-locking, Low rolling resistance on all surfaces
Storage	User configurable; available with several storage and accessory options

Display

Diagonal size	19" Standard
Display type	LCD
Options	Touch screen available

Power Supply

Battery	Nickel Metal Hydride (NiMH)
Input Voltage	100-240 VAC @ 5 amps.
Output Voltage	10.5 - 16 VDC
Battery run time	Up to 14 hours*
Charging Time, Full Charge	3 - 4 hours
Charging Status Indicator	LEDs with continuous readout and BatteryPro software
Power	500 Whr

On-board Computer

Select PCs or Thin Client devices from Dell, HP, IBM/Lenovo, Panasonic, Wyse, and many others, featuring Microsoft Windows, Intel Core Duo Processor, and Cisco CCX compatible Wireless LAN connectivity.

* Actual run time may vary depending on several factors such as technology configuration, battery age, usage pattern and power supply model/battery option. Run time is based on continuous use for a system using 35 Watts. Patent #6,493,220 and #6, 721,178

Flo 2700 Medication Workstations

